

View Online at <https://aerobasegroup.com/nsn/5935-00-171-1783>

Body Style:

Straight edge type w/mounting flange

Overall Length:

3.660 inches

Overall Height:

0.460 inches

Overall Width:

0.340 inches

Environmental Protection:

Moisture proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

3.410 inches

Board Accommodated Length:

2.970 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Mil-g-45204, type 2, class 1 military specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.