Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-171-1791

#### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

3.660 inches

# **Overall Height:**

0.460 inches

## **Overall Width:**

0.340 inches

#### **Environmental Protection:**

Moisture proof and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

#### 0.128 inches

**Distance Between Mounting Facility Centers:** 

3.410 inches

#### **Board Accommodated Length:**

2.970 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.070 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

1 row of contacts inserted board single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Polarization Method:**

Contact to contact polarizing keys

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# Insert Material Specification:

Mil-m-14, type sdi-5 military specification single material response single mating end

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 

18 single mating end single contact grouping

## Included Contact Type:

Bifurcated spring single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.