

View Online at <https://aerobasegroup.com/nsn/5935-00-172-4792>

Body Style:

Straight shape, internal coupling w/strain relief

Overall Diameter:

1.225 inches

Environmental Protection:

Heat resistant and vibration resistant

Cable Entrance Diameter:

Between 0.250 inches and 0.500 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

258.0 and 228.0 and 112.0 and 40.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium and nickel and chromate

Shell Surface Treatment Specification:

Qq-p-416 type 2 federal specification single treatment response

Shell Material Specification:

Qq-a-367, comp 6061, t6 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdc-f military specification single material response single mating end

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.