

View Online at https://aerobasegroup.com/nsn/5935-00-172-4853

Tŀ	iread Class:
2a	and 2a
Th	nread Direction:
Ri	ght-hand and right-hand
Вс	bdy Style:
St	raight shape, external coupling
0	verall Length:
1.:	317 inches
0	verall Height:
Be	etween 2.230 inches and 2.271 inches
0	verall Width:
Be	etween 2.230 inches and 2.271 inches
Ur	nthreaded Mounting Hole Diameter:
Be	etween 0.174 inches and 0.181 inches
Ce	enter To Center Distance Between Mounting Facilities Parallel To Height:
1.7	750 inches
Di	stance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.7	750 inches
Di	stance From Mounting Shoulder To Front Face:
0.	535 inches
Th	nreaded Device Type:
Ba	ack shell and coupling facility
Ма	ating End Quantity:
1	
Co	ontact Position Arrangement Style:
24	-61 single mating end
Co	ontact Removability:
Re	emovable single mating end single contact grouping
Po	Darization Method:
Ke	ey, multiple key groove
In	sert Position In Deg:
18	0.0
Sł	nell Type:
Sc	blid
Co	onnector Locking Method:
Ex	ternally threaded shell
Th	aread Length:
0.4	428 inches
Th	nready Qty Per Inch (tpi):
16	and 10
Th	nread Size:
1.8	375 inches and 2.000 inches

## NSN 5935-00-172-4853 Electrical Receptacle Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 61 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.061 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Un and double stub Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0