

NSN 5935-00-172-8110 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-172-8110 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.396 inches and 1.416 inches **Overall Height:** Between 3.115 inches and 3.135 inches **Overall Width:** Between 3.180 inches and 3.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.197 inches and 1.207 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.683 inches and 2.693 inches

Distance From Mounting Shoulder To Front Face:

Between 0.740 inches and 0.770 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

57 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

7.5 all mating ends single contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

NSN 5935-00-172-8110

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate all mating ends
Terminal Type:
Crimp all mating ends single contact grouping
Guide Design And Location:
Hexagon shape male post center at 6 oclock and hexagon shape male post right-hand at 6 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response all mating ends
Included Contact Type:
Round socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.114 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-19833 spec.