NSN 5935-00-173-1058

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-173-1058 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** Between 1.735 inches and 1.765 inches **Overall Width:** Between 1.735 inches and 1.765 inches **Unthreaded Mounting Hole Diameter:** Between 0.145 inches and 0.151 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.380 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.822 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-12 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 280.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.500 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-173-1058

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
3 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.