
NSN 5935-00-173-7300

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Blue **Body Style:** Threaded bushing mounted **Overall Length:** 0.672 inches Mounting Bushing Length: 0.438 inches **Body Length:** 0.672 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 750.0 ac Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.163 inches single finger Finger Accommodation Length: 0.562 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches **Capacitance In Picofarads:** 4.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic, diallyl phthalate insulator

NSN 5935-00-173-7300

Tip Jack - Page 2 of 2

Material:
Plastic diallyl phthalate insulator
Surface Treatment:
Tin terminal
Surface Treatment:
Nickel spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400

