NSN 5935-00-173-8249



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-173-8249 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 5.297 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.980 inches **Overall Height:** 5.031 inches **Overall Width:** 3.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: **2.718 inches Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 750.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Lever-pivot assembly spring action **Connector Cable Strain Relief Method:** Wedge-lock **Thread Length:** 0.500 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-173-8249

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0