Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-173-8249

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Rectangular shape
Overall Length:
5.297 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.980 inches
Overall Height:
5.031 inches
Overall Width:
3.406 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.718 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Lever-pivot assembly spring action
Connector Cable Strain Relief Method:
Wedge-lock
Thread Length:
0.500 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Terminal Location:
Back single mating end single contact grouping
Base single making one ongle contact grouping



#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Anodize

# Included Contact Quantity:

100 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## **Thread Series Designator:**

Unc

Shelf Life:

N/a

--

### Unit Of Measure:

Demilitarization:

No

----

Fiig:

A039b0