Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-174-0362

### **Body Style:**

Straight shape, external coupling

### **Overall Length:**

1.009 inches

### **Overall Height:**

1.047 inches

### **Overall Width:**

1.047 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

### Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

B4s single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Polarization Method:**

Key, multiple key groove

### **Insert Position In Deg:**

0.0

### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy



#### Shell Surface Treatment:

Cadmium and chromate

#### **Included Contact Quantity:**

4 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.004 gold grains, troy and 0.004 silver grains, troy

#### **Precious Material:**

Gold and silver

### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-38999 government specification

# Shelf Life:

N/a

Unit Of Measure:

# --

Demilitarization:

No

Fiig:

A039b0