## NSN 5935-00-175-4348

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-175-4348

Body Style:
Straight shape, flush mount
Overall Length:
1.060 inches
Overall Height:
3.080 inches
Overall Width:
2.000 inches
Environmental Protection:
Salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.060 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
67 all mating ends
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 2nd mating end 2nd contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings

Copper alloy all mating ends all contact groupings

#### **Contact Surface Treatment:**

Gold all mating ends all contact groupings

### **Insert Material:**

Plastic diallyl phthalate all mating ends

### **Terminal Type:**

Crimp all mating ends all contact groupings

### **Guide Design And Location:**

Hexagon shape male post right-hand at 1 oclock

# NSN 5935-00-175-4348

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
64 2nd mating end 2nd contact grouping
Included Contact Type:
Round pin all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.134 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0