# NSN 5935-00-175-4462

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-175-4462

2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
4.240 inches
Body Height:
0.765 inches
Environmental Protection:
Shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
3.900 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode

## NSN 5935-00-175-4462

Electrical Receptacle Connector - Page 2 of 2



Terminal Ty
-------------

Pin single mating end single contact grouping

## **Contact Material Specification:**

Qq-w-401, comp 401 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

66 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.066 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.