

View Online at <https://aerobasegroup.com/nsn/5935-00-175-5921>

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.709 inches

Overall Height:

1.453 inches

Overall Width:

1.453 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-16 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

27.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.016 gold grains, troy and 0.016 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0