

View Online at <https://aerobasegroup.com/nsn/5935-00-177-2095>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

Between 1.625 inches and 2.140 inches

**Overall Diameter:**

1.625 inches

**Environmental Protection:**

Pressure proof and moisture resistant and vibration resistant

**Cable Entrance Diameter:**

0.656 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-55 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

342.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Length:**

0.330 inches

**Thread Size:**

1.438 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Anodize

**Shell Material Specification:**

Qq-a-325, gr t6 federal specification single material response

**Included Contact Quantity:**

55 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.055 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-26500 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.