

View Online at https://aerobasegroup.com/nsn/5935-00-177-2285

Thread Class:	
2a and 2a	
Thread Direction:	
Right-hand and right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
2.125 inches	
Overall Height:	
Between 1.469 inches and 1.531 inches	
Overall Width:	
Between 1.469 inches and 1.531 inches	
Environmental Protection:	
Moisture resistant and salt water resistant	
Unthreaded Mounting Hole Diameter:	
Between 0.115 inches and 0.130 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.140 inches and 1.172 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 1.140 inches and 1.172 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.750 inches and 0.781 inches	
Threaded Device Type:	
Back shell and coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
20-27 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
22.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	



Connector Locking Method: Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.125 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef **Specification Data:** 81349-mil-c-5015 government specification Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0