NSN 5935-00-177-2761

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-177-2761

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

Between 1.170 inches and 1.210 inches

Overall Diameter:

Between 0.672 inches and 0.704 inches

Environmental Protection:

Shock proof and vibration resistant and salt water resistant

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 1st mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

10.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.190 inches and 0.500 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

NSN 5935-00-177-2761

Connector Adapter - Page 2 of 2



Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response
Shell Material Specification:
Qq-b-626 federal specification single material response
Included Contact Quantity:
1 2nd mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surface and shell surface gold
Precious Material And Weight:
0.110 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf and unef
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.