

View Online at <https://aerobasegroup.com/nsn/5935-00-178-8038>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.495 inches and 1.505 inches

Overall Diameter:

Between 0.682 inches and 0.692 inches

Threaded Device Type:

Coupling facility and coupling facility

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Length:

0.188 inches

Thready Qty Per Inch (tpi):

24 and 27

Thread Size:

0.625 inches and 0.750 inches

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Spec 46610 federal specification single material response 1st mating end all contact groupings

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end all contact groupings

Precious Material And Location:

Contact and shell surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0