## NSN 5935-00-183-9624

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-183-9624 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.125 inches **Overall Diameter:** 1.785 inches **Environmental Protection:** Hermetic **Distance From Mounting Shoulder To Front Face:** 1.000 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.218 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 79 number 16 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel alloy single mating end single contact grouping and iron alloy single mating end single contact grouping

## NSN 5935-00-183-9624

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1 or type 2, grade c, cl 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

	ina		

Crimp single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

**Passivate** 

**Included Contact Quantity:** 

79 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.079 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No Fiig:

1020h

Mil-std (military Standard):

Mil-g-45204 spec.