Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-184-6707

Body Style:
Straight shape
Overall Height:
1.390 inches
Overall Diameter:
Between 0.491 inches and 0.497 inches
Environmental Protection:
Salt water resistant and watertight
Cable Entrance Diameter:
Between 0.150 inches and 0.170 inches
Mating End Quantity:
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Cable Strain Relief Method:
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Qq-s-365, type 2, grade a federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Shell Material:
Rubber synthetic
Shell Material Specification:
Mil-std-417, type s, class sc615 military standard single material response
Insert Material Specification:

Mil-std-417, type s, class sc615 military standard single material response single mating end

NSN 5935-00-184-6707

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.005 silver grains, troy

Precious Material:

Silver

Test Data Document:

96906-ms27144 standard (includes industry or association standards, individual manufactureer standards, etc.).

Specification Data:

96906-ms27144-3 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-417 spec.