## NSN 5935-00-184-7603

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-184-7603 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.690 inches **Overall Height:** 0.530 inches **Overall Width:** 0.190 inches **Environmental Protection:** Vibration resistant **Distance Between Mounting Facility Centers:** 0.468 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.150 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-184-7603

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Quantity: 5 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surface gold Precious Material And Weight: 0.005 gold grains, troy Precious Material: Gold Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0