NSN 5935-00-185-1814

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-185-1814

View Online at https://aerobasegroup.com/nsn/5935-00-185-1814
Thread Class:
2a
Body Style:
Straight shape, external coupling
Overall Length:
1.406 inches
Overall Diameter:
0.688 inches
Environmental Protection:
Pressure proof
Distance From Mounting Shoulder To Front Face:
0.765 inches
Mounting Facility Thickness:
0.188 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
2
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Externally threaded shell
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms:
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size:
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material:
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment:
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver Shell Material Specification: Qq-b-626, comp 22 federal specification single material response
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver Shell Material Specification: Qq-b-626, comp 22 federal specification single material response Included Contact Quantity:
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver Shell Material Specification: Qq-b-626, comp 22 federal specification single material response Included Contact Quantity: 2 single mating end single contact grouping
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver Shell Material Specification: Qq-b-626, comp 22 federal specification single material response Included Contact Quantity: 2 single mating end single contact grouping
Solid Connector Locking Method: Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.438 inches Shell Material: Copper alloy Shell Surface Treatment: Silver Shell Material Specification: Qq-b-626, comp 22 federal specification single material response Included Contact Quantity: 2 single mating end single contact grouping Bushing Accommodation Hole Shape: Round w/flat

N/a

NSN 5935-00-185-1814

Connector Adapter - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

