## NSN 5935-00-185-4208

Electrical Plug Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-185-4208  |
|--|
| Body Style:  |
| Angle, shape, internal coupling  |
| Overall Length:  |
| 1.609 inches   |
| Overall Height:  |
| 1.000 inches   |
| Overall Diameter:  |
| 0.609 inches   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| Nonstd single mating end   |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Bayonet latch  |
| Connector Cable Strain Relief Method:  |
| Crimp type   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Insert Material:   |
| Plastic tetrafluoroethylene single mating end  |
| Contact Surface Treatment Specification:   |
| Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Surface Treatment:   |
| Gold   |
| Shell Surface Treatment Specification:   |
| Mil-g-45204, type 2, cl 2 military specification single treatment response   |
| Included Contact Quantity:   |
| 1 single mating end single contact grouping  |
| Included Contact Type:   |
| Coaxial socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact and shell surfaces gold  |

0.105 gold grains, troy

**Precious Material And Weight:** 

## NSN 5935-00-185-4208

Electrical Plug Connector - Page 2 of 2



| Precious Material:           |
|------------------------------|
| Gold                         |
| Shelf Life:                  |
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
| No                           |
| Fiig:                        |
| A039b0                       |
| Mil-std (military Standard): |

Mil-g-45204 spec.