NSN 5935-00-186-0470

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-186-0470 **Body Style:** Straight shape **Overall Length:** 2.729 inches **Overall Height:** 0.633 inches **Overall Width:** 0.494 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.086 inches **Distance Between Mounting Facility Centers:** 2.500 inches **Mating End Quantity: Contact Position Arrangement Style:** "c, 27w2" single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 2nd contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Spring friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:**

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-00-186-0470

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14f, type sdg military specification single material response single mating end

Included Contact Quantity:

25 single mating end 2nd contact grouping

Included Contact Type:

Coaxial socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.035 gold grains, troy and 0.035 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.