Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-186-0784

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight edge type
Overall Length:
3.200 inches
Overall Height:
0.437 inches
Overall Width:
Between 0.318 inches and 0.338 inches
Distance Between Mounting Facility Centers:
2.938 inches
Board Accommodated Length:
2.504 inches single board
Threaded Device Type:
Mounting hole
Board Accommodated Width:
0.156 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab colder lug single mating and single contact grouping

Tab, solder lug single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-19833, type gdi-30 military specification single material response single mating end **Included Contact Quantity:** 15 single mating end single contact grouping Included Contact Type: Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.