## NSN 5935-00-186-1733

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-186-1733

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.500 inches

**Environmental Protection:** 

Salt water resistant

**Distance From Mounting Shoulder To Front Face:** 

Between 0.400 inches and 0.460 inches

**Mounting Facility Thickness:** 

0.093 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:** 

1000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

**Connector Cable Strain Relief Method:** 

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36 and 36

**Thread Size:** 

0.250 inches and 0.250 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-00-186-1733

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel comp 305
Shell Surface Treatment:
Gold
Shell Material Specification:
Qq-s-763 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0