

View Online at <https://aerobasegroup.com/nsn/5935-00-189-1486>

Body Style:

Straight shape threaded

Overall Length:

0.891 inches

Overall Diameter:

1.312 inches

Environmental Protection:

Moisture resistant and salt water resistant and thermal shock resistant

Distance From Mounting Shoulder To Front Face:

Between 0.473 inches and 0.504 inches

Mounting Facility Thickness:

0.129 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-39 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Tin single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Surface Treatment:

Tin

Included Contact Quantity:

37 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Solder flange mounted

Test Data Document:

81349-milc26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0