Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-189-2208

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape threaded   |
| Overall Length:   |
| 0.954 inches  |
| Overall Diameter:   |
| Between 1.922 inches and 1.954 inches   |
| Environmental Protection:   |
| Moisture resistant and salt water resistant and vibration resistant                                 |
| Distance From Mounting Shoulder To Front Face:  |
| Between 0.433 inches and 0.443 inches   |
| Mounting Facility Thickness:  |
| Between 0.062 inches and 0.109 inches   |
| Threaded Device Type:   |
| Mounting bushing  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 16-6 single mating end  |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Bayonet pin   |
| Thread Size:  |
| 1.375 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Terminal Type:  |

Crimp single mating end single contact grouping



## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium

## Included Contact Quantity:

6 single mating end single contact grouping

# **Bushing Accommodation Hole Shape:**

Round

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surface gold and contact surface silver

## **Precious Material And Weight:**

0.030 gold grains, troy and 0.030 silver grains, troy

#### Precious Material:

Gold and silver

#### **Test Data Document:**

81349-milc38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

# Specification Data:

81349-mil-c-38999 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

### Fiig:

A039b0