

View Online at <https://aerobasegroup.com/nsn/5935-00-189-2943>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Green

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.938 inches and 0.969 inches

Mounting Bushing Length:

Between 0.418 inches and 0.438 inches

Body Length:

0.809 inches

Overall Diameter:

Between 0.313 inches and 0.375 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Test prod stepped single finger

Finger Accommodation Diameter:

0.068 inches and 0.088 inches single finger

Finger Accommodation Length:

0.150 inches and 0.170 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Type:

Turret

Material:

Plastic, diallyl phthalate insulator

Material:

Plastic diallyl phthalate insulator

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold spring

Surface Treatment:

Gold spring

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400