

View Online at <https://aerobasegroup.com/nsn/5935-00-189-3467>

Body Style:

Straight shape, flush mount

Overall Length:

1.388 inches

Overall Height:

Between 3.060 inches and 3.090 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.432 inches and 1.442 inches

Distance From Mounting Shoulder To Front Face:

Between 0.055 inches and 0.065 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

67 2nd mating end

Contact Removability:

Removable 1st mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

7.5 1st mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

7.5 1st mating end 3rd contact grouping

Polarization Method:

2 polarization posts

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

30.0 single mating end all contact groupings

Terminal Location:

Back 1st mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Terminal Type:

Solder well 2nd mating end 2nd contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.115 gold grains, troy and 0.115 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0