Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-189-4766

### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

3.268 inches

# **Overall Height:**

Between 0.445 inches and 0.465 inches

# **Overall Width:**

Between 0.333 inches and 0.353 inches

#### Distance Between Mounting Facility Centers:

Between 2.930 inches and 2.946 inches

### **Board Accommodated Length:**

2.510 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

### **Polarization Method:**

Contact to contact polarizing keys

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic phenolic single mating end

### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-19833, type @gdi-30f military specification single material response single mating end

# Included Contact Quantity:

30 single mating end single contact grouping

### Included Contact Type:

Leaf spring single mating end single contact grouping

### **Special Features:**

Polarizing key between pins 2 and 3

Electrical Receptacle Connector - Page 2 of 2



**Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy and 0.030 silver grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.