

View Online at <https://aerobasegroup.com/nsn/5935-00-189-6914>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.484 inches

Overall Diameter:

1.000 inches

Environmental Protection:

Explosion proof and pressure proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

12sl-844 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Potting type

Thread Size:

0.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Chromium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic silicone single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0