NSN 5935-00-190-0045

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-190-0045

Boo	dy Style:
Stra	aight shape, external coupling w/backshell
Ove	erall Length:
1.56	62 inches
Ove	erall Height:
1.56	62 inches
Ove	erall Width:
1.56	62 inches
Env	rironmental Protection:
Moi	sture resistant
Unt	hreaded Mounting Hole Diameter:
0.12	20 inches
Cer	nter To Center Distance Between Mounting Facilities Parallel To Height:
1.25	50 inches
Dis	tance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.25	50 inches
Dis	tance From Mounting Shoulder To Front Face:
0.55	56 inches
Mat	ing End Quantity:
1	
Cor	ntact Position Arrangement Style:
22-4	41 single mating end
Cor	ntact Removability:
Ren	novable single mating end all contact groupings
Cor	ntact Maximum Current Rating In Amps:
7.5	single mating end 2nd contact grouping
Pol	arization Method:
Key	way or multiple keyway
Inse	ert Position In Deg:
0.0	
She	ell Type:
Soli	d
Cor	nnector Locking Method:
Bay	ronet pin
Ter	minal Location:
Bac	k single mating end all contact groupings
Cor	ntact Material:
Cop	oper alloy single mating end all contact groupings
Cor	ntact Surface Treatment:
Gol	d single mating end all contact groupings and silver single mating end all contact groupings

Rubber single mating end

Insert Material:

NSN 5935-00-190-0045

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
27 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0