## NSN 5935-00-190-0070

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-190-0070

**Body Style:** Straight edge type **Overall Length:** 3.300 inches **Overall Height:** 1.110 inches **Overall Width:** 0.400 inches **Environmental Protection:** Moisture resistant and vibration resistant and thermal shock resistant **Distance Between Mounting Facility Centers:** 2.800 inches **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 3000.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Plastic polytetrafluoroethylene **Included Contact Quantity:** 1 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-190-0070

Electrical Receptacle Connector - Page 2 of 2



| Р | recious | Material | And | Location: |
|---|---------|----------|-----|-----------|
|---|---------|----------|-----|-----------|

Contact surface gold and contact surface silver

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0