

View Online at <https://aerobasegroup.com/nsn/5935-00-190-6060>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

Between 1.235 inches and 1.265 inches

Overall Width:

Between 0.385 inches and 0.395 inches

Mounting Hole Diameter:

0.112 inches

Body Mounting Hole Accommodation Length:

Between 0.735 inches and 0.765 inches

Body Mounting Hole Accommodation Width:

Between 0.385 inches and 0.395 inches

Mounting Hole Style:

Rectangular, w/two mounting holes/slots

Contact Maximum Current Rating In Amps:

3.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

8

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.995 inches and 1.005 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.157 inches and 0.167 inches

Polarization Type:

Colored dot

Projection Length Below Mounting Surface:

Between 0.344 inches and 0.374 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Dual in line

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300