## NSN 5935-00-191-5604

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-191-5604 **Thread Class:** 2a and 2g **Thread Pitch Diameters:** +2.000 to 2.011 inches and +2.986 to 3.000 inches **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.016 inches **Overall Height:** 3.250 inches **Overall Width:** 3.250 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.281 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.531 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.531 inches **Distance From Mounting Shoulder To Front Face:** 1.000 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 270.0

Shell Type:

Solid

## NSN 5935-00-191-5604

Electrical Receptacle Connector - Page 2 of 2



## **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end all contact groupings Thready Qty Per Inch (tpi): 18 and 10 **Thread Size:** 2.613 inches and 3.000 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 58 single mating end 3rd contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.066 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Acme and special acme Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0