# NSN 5935-00-192-4382

Straight shape, internal coupling w/backshell

**Thread Class:** 

Right-hand **Body Style:** 

**Thread Direction:** 

Overall Length: 1.080 inches

**Overall Diameter:** 

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-192-4382

0.870 inches	
Environmental Protection:	
Moisture resistant and salt water resistant	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
5 number 20 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
7500.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
255.0	
Shell Type:	
Solid	
Connector Locking Method:	
Internally threaded coupling ring	
Thready Qty Per Inch (tpi):	
32	
Thread Size:	
0.750 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy 360 single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and copper single mating end single contact grouping	

## NSN 5935-00-192-4382

Electrical Plug Connector - Page 2 of 2



nse			

Rubber silicone class q single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626, alloy 360, hh federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Copper alloy

#### **Shell Surface Treatment:**

Nickel

#### **Shell Surface Treatment Specification:**

Qq-n-290, @cl 1, type 2 federal specification single treatment response

#### **Shell Material Specification:**

Qq-b-626, alloy 360, hh federal specification single material response

#### **Insert Material Specification:**

Zz-r-765, cl 2a, grade 70 federal specification single material response single mating end or zz-r-765, cl 2b, grade 70 federal specification single material response single mating end

#### **Included Contact Quantity:**

5 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surface gold

#### **Precious Material And Weight:**

0.005 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Un

#### Shelf Life:

N/a

### **Unit Of Measure:**

**Demilitarization:** Nο

Fiig:

## A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.