NSN 5935-00-192-4828

Telephone Jack - Page 1 of 2

81349-mil-j-641 government specification



View Online at https://aerobasegroup.com/nsn/5935-00-192-4828

| Electrical insulation reature: |
|--|
| Insulated completely |
| Body Style: |
| Bushing mounted long frame |
| Overall Length: |
| 3.515 inches |
| Overall Height: |
| 0.859 inches |
| Mounting Hole Diameter: |
| 0.156 inches |
| Mounting Bushing Length: |
| 0.562 inches |
| Body Width: |
| 0.562 inches |
| Bushing Accommodation Hole Shape: |
| Round |
| Accommodated Finger Type: |
| Two conductor, round tip single finger |
| Finger Accommodation Diameter: |
| 0.252 inches single finger |
| Finger Accommodation Length: |
| 1.015 inches single finger |
| Mounting Bushing Diameter: |
| 0.448 inches |
| Bushing Thru-hole Accommodation Diameter: |
| 0.448 inches |
| Jack Contact Arrangement Designator: |
| J2-2a |
| Mounting Facility Type And Quantity: |
| 1 bushing and 1 unthreaded hole |
| Terminal Type: |
| Tab, solder lug |
| Material: |
| Any acceptable terminal |
| Surface Treatment: |
| Tin terminal |
| Surface Treatment: |
| Any acceptable contact |
| Test Data Document: |
| 81349-mil-j-641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |

NSN 5935-00-192-4828

Telephone Jack - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400