Contact surfaces gold

Electrical Receptacle Connector - Page 1 of 2



single contact grouping

View Online at https://aerobasegroup.com/nsn/5935-00-192-6149

Body Style:
Straight type
Overall Length:
2.410 inches
Overall Height:
0.328 inches
Overall Width:
0.660 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Distance Between Mounting Facility Centers:
2.164 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-p-19833, ty gdi-30 military specification single material response single mating end
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold



Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.