

View Online at <https://aerobasegroup.com/nsn/5935-00-192-6187>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.562 inches

Overall Height:

0.531 inches

Overall Width:

0.500 inches

Distance Between Mounting Facility Centers:

1.312 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.180 inches

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end and mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.