NSN 5935-00-194-6576

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-194-6576

Body Style:

Straight shape, external coupling strain relief

Overall Height:

1.688 inches

Overall Width:

1.688 inches

Body Length:

2.328 inches

Environmental Protection:

Moisture resistant

Unthreaded Mounting Hole Diameter:

0.147 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Cable Entrance Diameter:

0.800 inches

Distance From Mounting Shoulder To Front Face:

0.589 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

NSN 5935-00-194-6576

Electrical Receptacle Connector - Page 2 of 2



Back single	e mating end single contact grouping
Contact M	
	oy single mating end single contact grouping
	urface Treatment:
	e mating end single contact grouping and silver single mating end single contact grouping
Insert Mat	
	ngle mating end
Terminal ⁻	
	gle mating end single contact grouping
	ace Treatment:
Cadmium	
	ace Treatment Specification:
	type 2, cl 3 federal specification single treatment response
	Contact Quantity:
	nating end single contact grouping
	Contact Type:
	single mating end single contact grouping
	Material And Location:
Contact su	Irface gold and contact surface silver
Precious	
Gold and s	silver
Shelf Life:	:
N/a	
Unit Of Me	easure:
Demilitari	zation:
No	
Fiig:	
A039b0	