NSN 5935-00-194-8100



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-194-8100 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 6.930 inches **Overall Height:** 1.170 inches **Overall Width:** 0.360 inches **Distance Between Mounting Facility Centers:** 6.670 inches **Board Accommodated Length:** 6.250 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** 0.062 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Inter-contact polarizing keys Thread Length: 0.250 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-194-8100

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

98 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.098 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.