NSN 5935-00-195-3977

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-195-3977
Body Style:
Straight shape
Overall Length:
4.325 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.875 inches
Overall Height:
1.170 inches
Overall Width:
1.255 inches
Environmental Protection:
Corrosion resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.197 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
101 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1500.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping

Contact Material:

Nickel alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-195-3977

Mil-c-83723 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Mil-c-83723 military specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, class 1 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
101 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact srfaces gold
Precious Material And Weight:
0.101 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):