# NSN 5935-00-195-8591

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-195-8591

#### **Body Style:**

Straight shape, external coupling w/backshell

### **Overall Length:**

1.531 inches

# **Overall Height:**

1.578 inches

### **Overall Width:**

1.578 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.245 inches and 1.255 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.245 inches and 1.255 inches

#### Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.566 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

22-55 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

Plastic diallyl phthalate single mating end

**Insert Material:** 

---



# **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Insert Material Specification:** Mil-m-19833, type gdi-30 military specification single material response single mating end **Included Contact Quantity:** 55 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.055 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.