

View Online at <https://aerobasegroup.com/nsn/5935-00-195-8987>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, w/o cable clamp

**Overall Diameter:**

1.594 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Moisture resistant and salt water resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-11 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1750.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

2450.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Conduit nut

**Distance From Centerline To Connector End:**

3.031 inches

**Distance From Centerline To Cable End:**

2.344 inches

**Thread Size:**

1.188 inches and 1.375 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0