NSN 5935-00-195-9049

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-195-9049	
Thread Class:	
2a and 2a	
Thread Direction:	
Right-hand and right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.328 inches	
Overall Diameter:	
0.812 inches	
Cable Entrance Diameter:	
0.119 inches	
Distance From Mounting Shoulder To Front Face:	
0.703 inches	
Threaded Device Type:	
Coupling facility and mounting bushing	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
Tnc single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	
Connector Cable Strain Relief Method:	
Compression nut	
Thready Qty Per Inch (tpi):	
28 and 28	
Thread Size:	
0.438 inches and 0.438 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	

Contact Surface Treatment.

Silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

NSN 5935-00-195-9049

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Shell Material Specification:
Qq-b-626 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface and shell surface silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0