NSN 5935-00-196-7206

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-196-7206

Body Style:

Straight shape

Overall Length:

1.443 inches

Overall Width:

0.282 inches

Unthreaded Mounting Hole Diameter:

Between 0.096 inches and 0.100 inches

Distance Between Mounting Facility Centers:

1.193 inches

Mating End Quantity:

.

Contact Position Arrangement Style:

22 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Spring friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.022 gold grains, troy and 0.022 silver grains, troy

NSN 5935-00-196-7206

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|-----------------------------|
| Gold and silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-m-14 spec.