

View Online at <https://aerobasegroup.com/nsn/5935-00-197-6703>

Body Style:

Straight shape

Overall Length:

0.703 inches

Overall Height:

0.906 inches

Overall Width:

0.203 inches

Distance Between Mounting Facility Centers:

0.482 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

5 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1850.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

2590.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sgd-f military specification single material response single mating end

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.