# NSN 5935-00-198-3551

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-198-3551

**Body Style:** Straight shape, external coupling w/backshell Overall Length: 1.522 inches **Overall Diameter:** 1.142 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Mating End Quantity: Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 315.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Contact Surface Treatment Specification:** e federal specification 2nd treatment response single mating end single contact grouping

Mil-g-4502, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade

## **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium

### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

## **Included Contact Quantity:**

19 single mating end single contact grouping

# NSN 5935-00-198-3551

Mil-std (military Standard):

Mil-g-4502 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms3121 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0