NSN 5935-00-200-1016

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-200-1016

Straight edge type w/mounting flange

Overall Length:

3.505 inches

Overall Height:

0.770 inches

Overall Width:

0.248 inches

Environmental Protection:

Heat resistant and moisture resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.098 inches

Distance Between Mounting Facility Centers:

3.215 inches

Board Accommodated Length:

2.550 inches single board

Board Accommodated Width:

0.066 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

NSN 5935-00-200-1016

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 70 single mating end single contact grouping Included Contact Type: Curved pin single mating end single contact grouping Precious Material And Location: Contact surface gold Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):