

View Online at <https://aerobasegroup.com/nsn/5935-00-200-9377>

**Overall Length:**

Between 2.368 inches and 2.392 inches

**Overall Height:**

Between 0.598 inches and 0.697 inches

**Overall Width:**

0.248 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.171 inches

**Distance Between Mounting Facility Centers:**

2.090 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Qq-n-290 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 1 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

40 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-55302/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.